

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Name : Epoxy Resin High Temp #300
Product code : RB300

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Additive
Adhesives: Component

1.3. Details of the supplier of the safety data sheet

Nu Flow Technologies (2000) Inc.
1313 Boundary Rd.
L1J 6Z7 Oshawa, Ontario
CANADA

Attn: Mrs. Deborah Read
Tel: 905-433-5510
Email: dread@nuflowtech.com

1.4. Emergency telephone number

Country	Organization/Company	Address	Emergency number
MEXICO	Servicio de Informacion Toxicologica Sintox	Tintoreto #32 Edif. a Desp. Col. Nochebuena Mixcoac México, D.F.	1 800 009 2800 +52 55 5611 2634 /+52 55 5598 9095
UNITED STATES OF AMERICA	American Association of Poison Control Centers		1-800-222-1222

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Skin Irrit. 2 H315
Eye Irrit. 2A H319
Skin Sens. 1 H317
Carc. 2 H351

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

GHS08

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H351 - Suspected of causing cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P261 - Avoid breathing fume, vapors, mist
P264 - Wash hands thoroughly after handling
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear eye protection, protective clothing, protective gloves
P302+P352 - If on skin: Wash with plenty of soap and water
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention

Epoxy Resin High Temp #300

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P362+P364 - Take off contaminated clothing and wash it before reuse
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane	(CAS No) 1675-54-3	>= 80	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
Titanium(IV) oxide	(CAS No) 13463-67-7	1 - 5	Carc. 2, H351

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Suspected of causing cancer.
First-aid measures after inhalation	: Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Gently wash with plenty of soap and water. Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Rinse immediately with plenty of water. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause an allergic skin reaction.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
----------------------	--

Epoxy Resin High Temp #300

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid breathing fume, vapors, mist. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Wash skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat-ignition.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Epoxy Resin High Temp #300		
ACGIH	Not applicable	
OSHA	Not applicable	
2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane (1675-54-3)		
ACGIH	Not applicable	
OSHA	Not applicable	
Titanium(IV) oxide (13463-67-7)		
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³
ACGIH	Remark (ACGIH)	LRT irr; A3
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³

8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation.

Personal protective equipment : Protective clothing. Protective goggles. Gloves. Avoid all unnecessary exposure.



Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

Other information : Do not eat, drink or smoke during use.

Epoxy Resin High Temp #300

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: white
Odor	: Slight
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 300 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Solubility	: Water: Solubility in water of component(s) of the mixture : • 2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane: insoluble • Titanium(IV) oxide: 0,15 g/100ml
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
(Based on available data, the classification criteria are not met)

2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane (1675-54-3)

LD50 oral rat	11000 mg/kg (Rat)
---------------	-------------------

Epoxy Resin High Temp #300

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane (1675-54-3)	
LD50 dermal rabbit	20000 mg/kg (Rabbit)
ATE US (oral)	11000,000 mg/kg body weight
ATE US (dermal)	20000,000 mg/kg body weight

Titanium(IV) oxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg (Rat; OECD 425: Acute Oral Toxicity: Up-and-Down Procedure; Experimental value; > 5000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	> 6,8 mg/l/4h (Rat; Experimental value)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)Based on available data, the classification criteria are not met
Carcinogenicity	: Suspected of causing cancer.

2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane (1675-54-3)	
IARC group	3 - Not classifiable

Titanium(IV) oxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity (repeated exposure)	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Symptoms/injuries after inhalation	: May cause an allergic skin reaction.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	: Harmful to aquatic life with long lasting effects.
-----------------	--

Titanium(IV) oxide (13463-67-7)	
LC50 fish 1	> 1000 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	< 1000 mg/l (432 h; Daphnia magna; Static system)
LC50 fish 2	> 1 g/l (96 h; Leuciscus idus)
EC50 Daphnia 2	< 500 mg/l (720 h; Daphnia magna; Static system)
Threshold limit algae 1	61 mg/l (72 h; Pseudokirchneriella subcapitata)

12.2. Persistence and degradability

Epoxy Resin High Temp #300	
Persistence and degradability	May cause long-term adverse effects in the environment.

2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane (1675-54-3)	
Persistence and degradability	Biodegradability in water: no data available.

Titanium(IV) oxide (13463-67-7)	
Persistence and degradability	Biodegradability: Not applicable. Low potential for Mobility in soil.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable

Epoxy Resin High Temp #300

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Titanium(IV) oxide (13463-67-7)	
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

Epoxy Resin High Temp #300	
Bioaccumulative potential	Not established.

2,2-bis-[4(2,3-epoxypropoxy)phenyl]propane (1675-54-3)	
Bioaccumulative potential	Not bioaccumulative.

Titanium(IV) oxide (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not dangerous goods in terms of transport regulations

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Titanium(IV) oxide (13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2 H315

Eye Irrit. 2 H319

Skin Sens. 1 H317

Aquatic Chronic 3 H412

Full text of H-phrases: see section 16

Epoxy Resin High Temp #300

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xi; R36/38

R43

R52/53

Full text of R-phrases: see section 16

National regulations

Titanium(IV) oxide (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

No additional information available

SECTION 16: Other information

Revision date : 07/20/2015

Other information : None.


Full text of H-phrases:

Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
H227	Combustible liquid
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H351	Suspected of causing cancer

NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

* - Chronic (long-term) health effects may result from repeated overexposure

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal Protection : C

C - Safety glasses, Gloves, Synthetic apron

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.